



Huegin-Trietex GmbH
Dammstraße 5a
79588 Efringen-Kirchen
Germany

Phone +49 7628 9100 0
Fax +49 7628 9100 40
info@huegin-trietex.com
www.trietex.com

ZERTIFIKAT **Managementsystem**
in Übereinstimmung mit dem Standard
DIN EN ISO 9001:2015

Es wird bescheinigt, dass die Organisation
Huegin-Trietex GmbH
Dammstraße 5a
79588 Efringen-Kirchen

Das Managementsystem für den folgenden Leistungsbereich umfasst:
Spritzgussteile, Umgepölte Schläuche und Bänder,
Stanz- und Biegeteile, Spritzgusswerkzeuge,
Stanz- und Biegewerkzeuge, CNC Fräs- und
Drehteile, Antriebstechnik und Zubehör für
den innenliegenden Sonnenschutz

Das Zertifikat bezieht sich auf:
Zertifizierungsnummer: 01000042
Datum der Erstzertifizierung: 09.06.2015
Gültigkeit des Zertifikats bis: 22.06.2018

Prof. Dr. Grottel
Zertifizierungsstelle
Anwaltskanzlei/Region der Gültigkeit: 18.04.2012

Das Zertifikat ist Eigentum der ZICG Zertifizierung GmbH und kann auf Verlangen zurückgegeben werden.

Specifications Elite curtain track motor

Type	Asynchronous motor / DC
Voltage	230V and 110V autosensing
Power Input	65 watts
Rated Torque	1,5 Nm
Speed	180 mm/s
Limiting size	width 10m, height 4,5m, 60 kgs
Limit setting	auto detect, electronic
Dimensions *1	333 x 67,5 x 53 mm
Approvals	CE, ISO 9001
Radio receiver	integrated, 433 MHz
Control Options	230 volt switching, dry contacts, integrated radio control receiver
Dry contacts	Pin 1 - Serial connection Port B Pin 2 - Com Pin 3 - Direction 1 Pin 4 - Stop PIN 5 - Direction 2 PIN 6 - Serial Connection Port A
230 Volts contacts	1 - Neutral, permanently connected to neutral 2 - Power on = left drive 3 - Power on = right drive PE - Protective earth (ground) 4 - Power for electronic, permanently connected to Live

*1 Dimensions are without power plug and rail gear.


Technical data are subject to change.

Elite


Curtain Track Motor.




The new Elite series curtain track motor from Trietex. Intuitive touch operation, compatibility with all other Trietex curtain track components, silent movement and great value are only some of the major advantages. Motors can also be easily integrated into room control systems by direct 230v switching or by controlling the motor over dry contacts. In case of power failure the curtain can be moved easily by hand.




Intuitive operation - an easy pull at the curtain starts the moving in the corresponding direction.



Works with all runners and accessories of the Trietex curtain track rail system.



One rail gear - all options. The Elite also uses the standard Trietex rail gear that allows exchanging with all current Trietex motors. Also this motor can be retrofitted to an existing rail.



Well organized - all cables can be fixated with the cable guide.



Beside the 230 volt switching for directions you can also control the motor by means of dry contacts or with the integrated remote control receiver.



Different overlap options for wave flow or standard curtains and also in different lengths available. Special overlap arms for extreme bending radius of >250mm also available on request.

Attention!
Move the slider
above down to
secure motor.